

*The Signature
for Success*

Promotional & Marking Product Range

Spec. No. : PM238
Date of Issue : 26/04/00
Supersedes : Draft

Product Code - DS/2 Polyester
Adhesive Reference - RI-AHT/RI-AHT
Description - Clear polyester support

Face Material

Caliper - 12 microns (+/-10%)
Substance - 16 gsm (+/-10%)
Shrinkage - Nil
Recommended Life - 3 years

Adhesive

Adhesive Type - Permanent acrylic
Tack - High
Resistance to Sunlight - Very good
Minimum Application Temperature - +5°C
Service Temperature - -30 to +120°C
Cohesive Strength - High
Initial Adhesion - 1300 g/25mm
Adhesion at 48 Hours - 2000+ g/25mm

Release Liner

Type of Backing - Kraft-Clay ctd ss sil./1 side PE ctd ss sil.
Colour - W / W
Substance - 140 / 72 gsm (+/-10%)
Caliper - 150 / 80 microns (+/-10%)

Typical Applications: General mounting applications

Available width: 1.0m



Any values presented in this data sheet are typical. The information is given in good faith but without warranty.

Ritrama (UK) Limited, Lynwell Road,
Lyntown Trading Estate, Eccles,
Manchester M30 9QG, ENGLAND
Tel: 0161 786 1760
Fax: 0161 786 1761

Ritrama s.p.a.,
Via della Guerrina, 108,
20052 Monza, ITALY
Tel: (039) 839215
Telex: 330559 RITRAM I
Fax: (039) 834718

Ritrama Duramark,
800 Kasota Avenue SE,
Minneapolis, MN 55414, U.S.A.
Tel: (612) 378 2277
Fax: (612) 378 9327